

Safety/Lock Wire

Quality, Selection and Service



Spools

Spools are typically used in all applications of wire. We have the capabilities to supply wire on any type of spool. Standard spools come as 1, 2, 3, 5, 10, 25 and 40lb in either plastic or metal.

Safety/Lock Wire

Safety/Lock Wire is supplied in standard 1 lb spools or handi-cans. Larger spools are available upon request. We offer products that are compliant with the DFARS Special Metals clause.

Please specify DFARS Compliant when requesting either a quote or an order.



Handi-Cans

The wire is wrapped inside a cardboard or plastic canister. This packaging allows the wire to pay from the top center of the can. Each can typically holds 1 lb of wire.

Safety/Lock Wire Stock List

Alloy	Size	Specifications
302/304	0.015" – 0.062"	NASM20995C; MS20995C; QQW423; ASTMA580
305	0.015" – 0.062"	AMS5685
316	0.015" – 0.062"	QQW423; ASTMA580
321	0.015" – 0.062"	AMS5689
400	0.015" – 0.062"	NASM20995NC; MS20995NC; QQN281
600	0.015" – 0.062"	NASM20995N; MS20995N; QQW390; AMS5687
600 Oxide	0.015" – 0.062"	MS9226
Copper	0.015" – 0.062"	QQW343; MS20995CU; NASM20995CY; MS20995CY
Aluminum	0.015" – 0.062"	NASM20995AB; MS20995AB

Contact Us Today!

+1.800.232.3332 (Hanover, PA)
 +1.800.331.4044 (Houston, TX)
 +1.800.635.8296 (Ontario, CA)

+1.800.561.5903 (Mississauga, Canada)
 +1.353.68.31284 (Limerick, Ireland)

www.gerarddaniel.com