

PVC Tape

GDW-1335



Gerard Daniel's GDW-1335 is a high quality PVC film in combination with an ageing stable solvent rubber adhesive.

- High adhesive force
- Flexible and supple
- Self-extinguishing
- Roll Size: 1"x36 yard, 1.5"x36 yard, 2"x36 yard

Material Property Data

TOTAL THICKNESS	5 MIL	EN60454-2-1995
ADHESION TO STEEL	16.44 oz/in	EN60454-2-1995
ADHESION TO BACKING	13.70 oz/in	EN60454-2-1995
TENSILE STRENGTH	8.5 lb/in	EN60454-2-1995
FLAMMABILITY	SELF-EXTINGUISHING	EN60454-2-1995
INSULATION RESISTANCE	1.0X10 ¹¹ OHMS MIN	EN60454-2-1995

STORAGE & SHELF LIFE: 12 months when stored at 70°F / 50% relative humidity out of direct sunlight.

SURFACE PREPARATION: It is essential, as with all pressure-sensitive tapes, that the surface to which the tape is applied must be clean, dry, free of grease, oil or other contaminants.

PRODUCT USE: It is essential that the user evaluate the GDW tape product to determine whether it is fit for a particular purpose and user's method of application. Good results will be obtained when applied to a clean, dry surface with a suitable pressure on GDW tape between 50° - 105°F.

WARRANTY & REMEDY: Your exclusive remedy & GDW tape obligation shall be, at GDW's option, to replace or repair the GDW tape product or refund the purchase price of the GDW tape product.

All values are nominal